



RageTurf Motivate & Rally

RageTurf features a dense, textured polyethylene surface layer fusion bonded through patented itsTRU™ technology to either a 5mm (Motivate) or 12mm (Rally) vulcanized composition rubber base layer. While too abrasive to fall or dive on, this consistent and tight surface is ideal for all footwork drills and sled work. Available in 4 colors, RageTurf Motivate & Rally can handle the weight drop of moderate free weights, making it ideal for functional training.

MARKETS

- Fitness
- Student Rec
- Sports

APPLICATIONS

- Functional Training
- Consumer Spaces


BENEFITS

- No infill needed
- Ergonomic
- Acoustic
- Durable
- Portable / Easy to Install (Rally - Interlocking Tiles)


PRODUCT INFORMATION

Nominal Dimensions:

Available as a standard in rolls and interlocking tiles. Talk to your local agent to determine availability, pricing, minimums, and lead times.

 Rolls:
Motive: 17mm (12mm + 5mm) x 72" (1.83m) x 35LF (10.67m)
Rally: 24mm (12mm + 12mm) x 72" (1.83m) x 25LF (7.62m)

 Interlocking Tiles:
Rally: 24mm (12mm + 12mm) x 23" (58.42cm) x 46" (1.17m)

 Interlocking Turf Reducer:
¾" x 12" x 46"

Options:

[Click here to view more information on accessories](#)

Color Options:

[Click here to view colors](#)

TECHNICAL DETAILS

Performance Criteria	Test Standard	Typical Results Motive Rally	
Force Reduction	Deltec	30.8%	47.1%
Energy Restitution	Deltec	46.6%	41.0%
Vertical Deformation	Deltec	3.8mm	4.9mm
G-Max	Clegg	192	84
Tufted Pile Height		.47"	.47"
Pill Test / Flammability	ASTM D2859	Pass	Pass
Coefficient of Friction	ASTM D2047	0.87 (dry)	0.87 (dry)

THE NRG FACTOR

