



RageTurf UltraTile

RageTurf UltraTile features a dense, textured polyethylene surface layer that is factory fusion bonded to a molded composition rubber base. While too abrasive to fall or dive on, this consistent and tight surface is ideal for all footwork drills and can be used with Performance UltraTile. This 24-by-24-by-1-inch modular turf tile offers enhanced shock absorption against impact in moderate to extreme weight drop applications.



MARKETS

- Fitness
- Student Rec
- Sports

APPLICATIONS

- Functional Training
- Free Weights
- Therapy / Rehab
- Outdoor


BENEFITS


- Durable
- Sustainable
- Ease of maintenance
- Slip-resistant
- Easy installation with Quad Blok installation system


PRODUCT INFORMATION


Nominal Dimensions:

Available as a standard in molded tiles. Talk to your local agent to determine availability, pricing, minimums, and lead times.

 1" (25.4mm) x 24" (0.61m) x 24" (0.61m)

 ADA Ramp:
12" (305mm) x 48" (1.22m)
Thickness: 1" (25.4mm)

 Reducers:
4" (102mm) x 48" (1.22m)
Thickness: 1" (25.4mm)


 Quad Blok:
1/2" H x 4 3/4" x 4 3/4"
Adhesive = 1 Tube / 15 Quad Bloks

Color Options:
[Click here to view colors](#)

THE NRG FACTOR

NRG


=



60.3%

Force Reduction


Absorption of impact energy




36.9%

Energy Restitution


Useful return of impact energy



Safety



Ergonomics



Acoustics



TECHNICAL DETAILS

Performance Criteria	Test Standard	Typical Results
Force Reduction	Deltec	60.3%
Energy Restitution	Deltec	36.9%
Vertical Deformation	Deltec	7.2mm
G-Max	Clegg	52
Tufted Pile Height		.47"
Pill Test / Flammability	ASTM D2859	Pass
Coefficient of Friction	ASTM D2047	0.87 (dry)